




For Superior Strength, Durability




(A) 22-Gauge Medium Duty, Box "W" shelves offer 600 lb. capacity* for storage of aerosols, tools, drills, safety supplies, etc.



(B) 20-Gauge, Heavy Duty, Box "W" shelves provide 900 lb. capacity* to hold grinders, wheels, gears, sprockets, and other similar articles.



(C) 18-Gauge Extra Heavy Duty, Box "W" shelves deliver 1300 lb. capacity* for storing motors, pumps, and other heavy equipment.



(D) 18-Gauge Traditional flanged shelves afford 750 lb. capacity* for electrical fittings, clamps, bearings, etc.

36" Closed Shelving Sections – 84" High

For 96"h and 120"h Upright Assemblies, Parts and Components, see pages 18-19.

| No. of Shelves | 36" w x 12" d x 84" h | | 36" w x 18" d x 84" h | | 36" w x 24" d x 84" h | |
|---|-----------------------|---------|-----------------------|---------|-----------------------|---------|
| | STARTERS | ADD-ONS | STARTERS | ADD-ONS | STARTERS | ADD-ONS |
| (A) 22-GAUGE MEDIUM DUTY, BOX "W" SHELVING (maximum capacity: 600 lbs. per shelf*) | | | | | | |
| 5 | 8037SM | 8037M | 8038SM | 8038M | 8039SM | 8039M |
| 6 | 8260SM | 8260M | 8261SM | 8261M | 8262SM | 8262M |
| 6** | 8270SM | 8270M | 8271SM | 8271M | 8272SM | 8272M |
| 7 | 8090SM | 8090M | 8091SM | 8091M | 8092SM | 8092M |
| 8 | 8080SM | 8080M | 8081SM | 8081M | 8082SM | 8082M |
| (B) 20-GAUGE HEAVY DUTY, BOX "W" SHELVING (maximum capacity: 900 lbs. per shelf*) | | | | | | |
| 5 | 8037SH | 8037H | 8038SH | 8038H | 8039SH | 8039H |
| 6 | 8260SH | 8260H | 8261SH | 8261H | 8262SH | 8262H |
| 6** | 8270SH | 8270H | 8271SH | 8271H | 8272SH | 8272H |
| 7 | 8090SH | 8090H | 8091SH | 8091H | 8092SH | 8092H |
| 8 | 8080SH | 8080H | 8081SH | 8081H | 8082SH | 8082H |
| (C) 18-GAUGE EXTRA HEAVY DUTY, BOX "W" SHELVING (maximum capacity: 1300 lbs. per shelf*) | | | | | | |
| 5 | 8037SX | 8037X | 8038SX | 8038X | 8039SX | 8039X |
| 6 | 8260SX | 8260X | 8261SX | 8261X | 8262SX | 8262X |
| 6** | 8270SX | 8270X | 8271SX | 8271X | 8272SX | 8272X |
| (D) 18-GAUGE TRADITIONAL FLANGED SHELVING (maximum capacity: 750 lbs. per shelf*) | | | | | | |
| 5 | 8037S | 8037 | 8038S | 8038 | 8039S | 8039 |
| 6 | 8260S | 8260 | 8261S | 8261 | 8262S | 8262 |
| 6** | 8270S | 8270 | 8271S | 8271 | 8272S | 8272 |
| 7 | 8090S | 8090 | 8091S | 8091 | 8092S | 8092 |
| 8 | 8080S | 8080 | 8081S | 8081 | 8082S | 8082 |

*NOTE: Capacities are based on evenly distributed load. See page 3. Maximum load capacity: 8000 lbs. per section.

**NOTE: Back open with lateral cross brace.